

EzLogger Pro

EzLogger Pro is a self-developed monitoring device by GoodWe. In combination with a GoodWe solar inverter, it can easily read and record all key plant data and constantly transmit the data to the GoodWe portal via internet.



Communication distance up to 1000m



Connectivity for up to 60 devices at once



Data breakpoint resume



Encrypted data transmission process

Communication Management

Communication	Inverter Communication	3 × RS485
	Third-party equipment communication	1 × RS485
	Ethernet Communication	10 / 100M
Number of Managed Devices	RS485	60 (The number of devices connected to a single RS485 port shall not exceed 20)
Communication Distance	RS485 (m)	1000 (Shielded twisted pair wire shall be used)
	Ethernet (m)	100

General Parameters

General Parameters	Power Adapter	Input: 100 ~ 240Vac, 50 / 60Hz; output: 12Vdc 1.5A
	Power Consumption (W)	General 3, Maximum 6
	Storage Capacity	16MB, expandable to 8GB through an optional SD card
	Dimensions (L × W × H mm)	190 × 118 × 37
	Weight (g)	500
	Operating Temperature Range (°C)	-20 ~ +60
	Relative Humidity	5% ~ 95% (non-condensing)
	Ingress Protection Rating	IP20
	Installation Methods	Wall mounting, table surface mounting, rail mounting
	User Interface	8 LED indicators

*: Please visit GoodWe website for the latest certificates.

*: All pictures shown are for reference only. Actual appearance may vary.